



**Better Fuel
Economy
Reduced
NOx
Pollution
Lower
Particulate
Emissions**

BlueCat® AdBlue Reducing Agent to DIN70070 standard for the SCR Exhaust after-treatment in Euro4 or Euro5 diesel engines

Container can be exchanged with all security seals intact for full refund of deposit.

Key Information from the Material Safety Data Sheet

- AdBlue is an aqueous solution of 32.5 % wt/wt of urea. The product is of very high purity and its consistent quality is secured through the industrial standard DIN V 70070 and is licenced by the VDA.
- Ingestion of insignificant quantities should not be a cause for concern. If swallowed, do NOT induce vomiting. If vomiting occurs naturally, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Although the material is not classed as an irritant, direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness.
- AdBlue can induce inflammation of the skin following prolonged contact or immersion. Wear latex gloves.
- Slippery when spilt. Clean up all spills immediately.
- BlueCat is not flammable. Use water to control fires involving

BlueCat provided that water is compatible with burning materials.

- Store in original container. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from foodstuff containers.
- Safety Phrase S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Learn more at http://www.blue-cat.biz/bluecat_msds.htm

Protect against direct sunlight. Storable at least for one year between -5 and +25°C.

BlueCat AdBlue Solutions,
a division of J & H Bunn Ltd.,
South Beach Parade, Great Yarmouth
Norfolk NR30 3QA, UK.
Call Us Free 08000 ADBLUE (08000 232583)
Email: info@blue-cat.biz
Web: www.blue-cat.biz



By Appointment to H.M. The Queen
Manufacturers of Agricultural Fertilisers
J & H Bunn Ltd Great Yarmouth